

PD140SVR

ceia An ISO 9001 Company CERTIFIED

GSA Contract Holder

VERY HIGH SENSITIVITY ENHANCED HAND HELD METAL DETECTOR

- Very High Sensitivity
- Detection of both magnetic and non-magnetic metals
- Optical, acoustical and vibration alarm
- Long battery life
- Special ergonomic shape
- Very high Reliability
- Easy to use
- Self-Calibrating
- Fast inductive battery charger



THE SPECIAL ERGONOMIC SHAPE OF THE DEVICE ALLOWS INSPECTION WITHOUT THE INTERFERENCE OF THE OPERATOR'S FINGERS



SUPERIOR DETECTION,
ERGONOMICS,
VERY COMFORTABLE
TO USE



V140 CARRYING CASE
WITH BATTERY CHARGER



www.ceia-usa.com

PD140SVR ENHANCED HAND HELD METAL DETECTOR



The PD140SVR Enhanced Hand Held Metal Detector is a high sensitivity device designed to detect magnetic and non-magnetic metal masses. The unit can be used to detect weapons, detonators and other small pieces of metal concealed in baggage or correspondence.

The **bidirectional detection probe allows both sides to detect metals evenly.** The sensitivity of the surface is enhanced by the shape making operation of the device reliable and easy to operate.

The device is supplied with a standard test piece for functional verification. Custom calibration samples can be supplied in accordance with the Security Regulations in force.

TECHNICAL FEATURES

POWER SUPPLY	9V rechargeable Ni-MH battery
THREE-POSITION SWITCH WITH SELECTION OF TWO DIFFERENT ALARM MODES	Simultaneous optical and acoustic alarm. Built-in buzzer (75 dBA at a distance of 90 cm) Optical alarm and handle vibration
PRE-CALIBRATED SENSITIVITY THAT CAN BE MODIFIED BY USING AN INTERNAL TRIMMER	
BATTERY LIFE*	Optical and acoustic alarm: 40 hours typical** Optical and vibration alarm: 30 hours typical**
INDICATOR LAMPS FOR	Power on (green light) Alarm (red light) Low battery charge (blinking yellow light)
FIVE DIFFERENT ALARM TONES, SELECTED FROM THE FACTORY, IDENTIFIED BY THE LAST DIGIT OF THE SERIAL NUMBER	
OPERATING TEMPERATURE	5°F to 149°F (relative humidity: 0 to 95%)
Manufactured in grey, SHOCK-RESISTANT POLYCARBONATE and ABS BLEND	
DIMENSIONS	13.39" x 3.15" x 2.16" (340 x 80 x 55 mm)
WEIGHT (WITH BATTERY)	0.88 lb (0.400 kg.)
CONFORMS TO THE INTERNATIONAL STANDARDS CURRENTLY APPLICABLE for electrical safety, E.M.C. and to the applicable CE regulations	
* 10% alarm operation , 90% quiescent operation ** NiMH 9V – 150mAh cell	

OPERATOR CONTROLS AND SIGNALLING DEVICES



- 1 ALARM** **Red Light:** Alarm Signalling
- 2 LOW BATTERY** **Yellow light:** Low Battery Signalling (blinking)
- 3 POWER** **Green light:** "Power on" and "Ready" status Signalling. When charging on the BC140F, indicates the status of the charge
- 4 POWER/MODE** Switch
 - **Left position:** visual and audible alarm signalling
 - **Right position:** visual and vibration alarm signalling
- 5 ALARM BUZZER**

BC140F

FAST INDUCTIVE BATTERY CHARGER

The BC140F unit provides recharging, without electrical contact, of the NiMH batteries in the PD140SVR Metal Detectors. The BC140F battery charger is designed to be able to be connected in cascade with other similar devices.

TECHNICAL FEATURES

POWER SUPPLY: 90-265Vrms, 50/60 Hz, 4 W
RECHARGING TIME: 4 hours or less (complete cycle)
ON/OFF switch with indicator lamp
Connection in cascade with other similar devices (up to 20 units)
DIMENSIONS: 3.2" x 6.1" x 3.8" (ht) [82 x 155 x 97 (h) mm]
WEIGHT: 1.1 lb (0.500 kg)
LENGTH OF MAINS CABLE: 5.91 ft (1.80 m)
Length of cable for connecting units in cascade: 6.7" (0.17 m)
Manufactured in grey, shock-resistant ABS
Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable CE regulations

V140

CARRYING CASE

The V140 carrying-case, in shock-resistant material, is designed to contain the following items: a PD140SVR Hand Held Metal Detector, a test piece, a BC140F fast battery-charger, a power supply cable and the instructions for use.

TECHNICAL FEATURES

DIMENSIONS: 17.5" x 11.8" x 7" (ht) [445 x 300 x 180 mm]
WEIGHT: 5 lb (2.3 kg) including PD140SVR and battery charger
Shock-resistant ABS construction and the special storage compartments make the V140 carrying-case the ideal, safest and most compact means of transporting the PD140SVR
Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable CE regulations



Belt holster



GREEN LED
blinking: charge in progress;
steadily after blinking: charge completed

POWER LAMP
ON/OFF SWITCH

BC140F



CEIA USA Ltd - 9155 Dutton Drive, Twinsburg OH - 44087 USA
Phone: 330-405 3190 - Fax 330-405 3196 - e-mail: sales@ceia-usa.com

www.ceia-usa.com

CEIA USA reserves the right to make changes, at any moment and without notice, to the models (including programming), their accessories and options, to the prices and conditions of sale

Call 888-532-CEIA

DP100K0002v1000US-46777